

**JUKI**

# MO-6800S Series

High-speed, Overlock / Safety Stitch Machine



The advanced overlock / safety stitch machine is easier to use and promises superior cost effectiveness.



MO-6816S

# MO-6800S

High-speed, Overlock / Safety Stitch Machine

SERIES

# MO-6800S SERIES

This advanced overlock / safety stitch machine is easier to use and promises superior cost effectiveness.

The MO-6800S Series responds to various kinds of sewing materials and processes, producing delicate and beautiful soft-to-the-touch seams while further reducing operating noise as well as increasing durability. This advanced overlock / safety stitch machine is easier to use and promises superior cost-effectiveness.

The machine achieves beautifully finished seams of improved quality even when run at a high speed.

The machine is widely applicable to the sewing of light- to heavy-weight materials. Since the machine is provided with a needle thread take-up mechanism and a looper thread take-up lever, it ensures high-quality, well-tensed and soft seams with a beautiful texture which flexibly correspond to the elasticity of the materials even when run at speeds as high as 7,000 sti/min. In addition, the machine has a wider and brighter needle entry and provides improved responsiveness to the materials, thereby helping the operator use the machine more easily. The optimally-balanced design of the machine reduces both operating noise and vibration, contributing to more comfortable sewing work.



MO-6814S

The machine is provided with functions which contribute to easier operation.

The differential-feed micro-adjustment mechanism, external increasing of the differential feed ratio and the main feed dog height can all be adjustable on the front face of the sewing machine with a screwdriver. The machine is provided as standard with functions which enable easy and best-suited adjustments according to the material to be used.



Differential-feed micro-adjustment mechanism



For runstitch / MO-6816S-FF6-30H

## DEVICES AND ATTACHMENTS

Model	Part No.	Description
<b>Chain-off thread trimming device</b>		
T053	70000081	Pneumatic flat cutter
T054	70000082	Pneumatic side cutter (for overlock machine)
<b>Pneumatic chain-off thread suction device</b>		
MC904 / MC907	70000083 / 70000102	Specific to chain-off thread, pedal-operated clutch motor / servo motor
MC905 / MC908	70000084 / 70000103	MC904 / MC907 + Air type auto-lifter clutch motor / servo motor
MC906 / MC909	70000085 / 70000104	Pneumatic chain-off thread + cloth chips clutch motor / servo motor
MC910 / MC911	70000106 / 70000107	MC906 / MC909 + Air type auto-lifter clutch motor / servo motor

### [Reference]

Combination table of "chain-off thread suction device" and "auto-lifter" which correspond to "chain-off thread trimming device".

Chain-off thread suction device	Chain-off thread suction device	Auto-lifter
T053 or T054	MC904 / MC907	Clutch motor / servo motor
	MC905 / MC908	Air type auto-lifter clutch motor / servo motor
	MC906 / MC909	Clutch motor / servo motor
	MC910 / MC911	Air type auto-lifter clutch motor / servo motor

Model	Part No.	Description	Feature
<b>Gathering device</b>			
S206	70000089	Swing-type gathering device (interlocked with pedal / for overlock machine)	The attachment opens with the presser foot pedal. This facilitates material setting on the machine. Furthermore, knee-control type differential-feed adjusting device is built in the attachment. It controls a differential-feed ratio as desired, thereby enabling the operator to make beautiful gathers.
S207	70000090	Swing-type gathering device (interlocked with pedal / for safety stitch machine)(DF6)	
S208	70000091	Swing-type gathering device (interlocked with pedal / for safety stitch machine)(FF6)	
<b>Guide, tape guide</b>			
H253	40159861	Cloth edge guide ruler (for overlock machine)	A swing type edge guide.
H254	40159862	Cloth edge guide ruler (for safety stitch machine)	
Q143	40159863	Tape guide	This attachment is used attached on the machine head (face plate). It is used for tapes with the width of 7mm or less.
<b>Feller, Binder</b>			
N080	70000095	Reinforcement tape attachment binder	This binder binds the edge of a pocket bag while cutting round its periphery.
<b>Option</b>			
—	40159749	Micro-lifter	The micro-lifter is suited to fine adjustments of the lifting amount of the presser foot so as to prevent puckering.
R040	70000098	Tape holder	Table-mounting type tape folder
Z065	70000092	Square upper knife (for overlock machine)	
Z067	70000093	Square upper knife (for safety stitch machine)	

## SUBCLASS MACHINE LIST

Seams	Model No.	Materials	Number of needles	Number of threads	Needle gauge (mm)	Overriding width	Number of feed dog rows	Stitch length (mm)	Bottom differential feed ratio	Presser lifting amount (mm)	Needle system	Max sewing speed (sti/min)	Remarks
-------	-----------	-----------	-------------------	-------------------	-------------------	------------------	-------------------------	--------------------	--------------------------------	-----------------------------	---------------	----------------------------	---------

### [ 1-needle overlock ]

For runstitching in general fabric



MO-6804S-0E4-30H	L-M	1	3	—	4.0	2	3.8	1:0.7~1:2	6.0	DCx27 #11	7,000	
------------------	-----	---	---	---	-----	---	-----	-----------	-----	-----------	-------	--

### For rolled hemming (folded downward)

MO-6804S-0A4-150	EL-L	1	3	—	1.5	2	3.8	1:0.7~1:2	6.0	DCx1 #8	7,000	
------------------	------	---	---	---	-----	---	-----	-----------	-----	---------	-------	--

### [ 2-needle overlock ]

For runstitching in general fabric



MO-6814S-BD6-30H	L-M	2	4	2.0	3.0	3	3.8	1:0.7~1:2	5.5	DCx27 #11	7,000	
MO-6814S-BE6-40H	M-H	2	4	2.0	4.0	3	3.8	1:0.7~1:2	5.5	DCx27 #11	6,500	

### For tape attaching G44: Tape attaching presser foot Q143: Tape guide



MO-6814S-BD6-24H/ G44/Q143	L-M	2	4	2.0	3.0	3	3.8	1:0.7~1:2	5.5	DCx27 #9	7,000	
MO-6814S-BE6-24H/ G44/Q143		2	4	2.0	4.0	3	3.8	1:0.7~1:2	5.5	DCx27 #9	7,000	
MO-6814S-BE6-44H/ G44/Q143	M-H	2	4	2.0	4.0	3	3.8	1:0.7~1:2	7.0	DCx27 #14	6,500	

### [ Safety stitching ]

For runstitching in general fabric



MO-6816S-DE6-30H	L-M	2	5	3.0	4.0	3	3.8	1:0.7~1:2	5.5	DCx27 #11	7,000	
MO-6816S-FF6-30H		2	5	5.0	5.0	3	3.8	1:0.7~1:2	5.5	DCx27 #11	7,000	
MO-6816S-FF6-50H	M-H	2	5	5.0	5.0	3	3.8	1:0.7~1:2	7.0	DCx27 #16	6,500	
MO-6816S-FH6-50H		2	5	5.0	6.4	3	3.8	1:0.7~1:2	7.0	DCx27 #16	6,500	

### For rolling-in tape N075: Clean finish top and bottom



MO-6845S-FF6-360/ N075	M-H	2	4	5.0	5.0	3	3.8	1:0.7~1:2	5.0	DCx27 #14	7,000	2-needle type for double-chainstitch on pocket bags
------------------------	-----	---	---	-----	-----	---	-----	-----------	-----	-----------	-------	---

### [ 3-needle safety stitching ]



MO-6843S-1D6-40H	M-H	3	6	5.0+2.0	3.0	3	3.8	1:0.7~1:2	6.5	DCx27 #11	7,000	
MO-6843S-2D6-40H		3	6	3.0+2.0	3.0	3	3.8	1:0.7~1:2	6.5	DCx27 #11	7,000	

\*"sti/min" stands for "Stitches per Minute."

### Sewn product pictogram



### JUKI ECO PRODUCTS

The MO-6800S is an eco-friendly product which complies with JUKI ECO PRODUCTS standards for protecting the environment.



The sewing machine complies with the "Juki Group Green Procurement Guidelines" on the use of hazardous substances, which is stricter than other restrictions, such as those of the RoHS Directive.

For details of JUKI ECO PRODUCTS, refer to: [http://www.juki.co.jp/eco\\_e/index.html](http://www.juki.co.jp/eco_e/index.html)

\*The RoHS Directive is an EU Directive limiting the use of 6 hazardous substances (lead, hexavalent chromium, mercury, cadmium, PBB and PBDE) in electrical and electronic equipment. The Juki Green Procurement Guideline is the voluntarily established criteria to eliminate not only the aforementioned six substances, but also other ones which also adversely affect the environment.

