

LU2-4710-B1T / -4730-B1T

Lock-stitch Machine with Automatic Undertrimmer(Compound Feed type)  
Single Needle(LU2-4710-B1T) / Double Needle(LU2-4730-B1T)

- Compound feed high function sewing machine suitable for thick materials such as automobile seats, air bags and leather products
- High Walk feature and instantaneous changeover of the alternating presser foot amount at high speeds
- LIMISERVO motor mounted further enhancing compact size, light weight and functions



Model		LU2-4710-B1T			LU2-4730-B1T	
Applications		Heavy				
Max. speed(r.p.m)	speed (r.p.m)	reciprocal st. (mm)	stitch length (mm)	speed (r.p.m)	reciprocal st. (mm)	stitch length (mm)
	3,000	2	0 - 6	2,500	2	0 - 6
	2,700	3	0 - 6	2,300	3	0 - 6
	2,000	5 - 6	6 - 9	2,000	5 - 6	6 - 9
Max. stitch length(mm)		9				
Presser-foot clearance(mm)		Knee/Hand:16/9				
Needle		DPX17#23				
Alternating	movement(mm)	2 - 6				
	stroke adj.	Dial				
	instant adj.	Air cylinder				
Touch back		installed				
Hook		Large				
Bobbin		Aluminum trimmer type				
Needle gauge(mm)		-			Standard:3.2 Special:6.4, 12.7, 19, 25.4mm	
Automatic lifter (Air)		Option: AA-G100-PFL-15				
Weight(kg)		47				

High Walk Step Control

(Option) AA-G004-500