

**NEW**

**CONSEW** Since 1898

# Model 5457RB-7DD-DSM

## ZIG-ZAG / DECORATIVE STITCHING / DIRECT-DRIVE

*Energy saving ZigZag machine that makes Beautiful Stitches*

With

Electronic control

Auto Reverse

Auto Needle Position

Mini Self Oiling System

Energy Saving Servo System

Large Capacity for Sewing Patterns


Rotary Takeup

Auto trimmer

Adoptive Feed



Titanium coated Hook



Servo Motor Control



Outstandingly Beautiful  
Stitches

**HIGH-SPEED  
DIRECT-DRIVE  
COMPUTERIZED**

**ZIG-ZAG MACHINE**















# Model 5457RB-7DD-DSM

## APPLICATIONS

- Decorative Zig-Zag stitching on thin, medium and thick fabrics.
- For lingerie, womens jackets, collars attaching lace, elastic band, bottom hemming, edge stitching, butted seaming, applique and similar operations

## FEATURES

- Direct Drive servo motor system dramatically improves efficiency
- Servo motor controlled feed dog interacts with the digital system and stitch counter to create decorative stitches
- Mini oil lubrication system, ensures clean, smooth sewing.
- Multi-function color LCD touch screen operating panel.
- Capable of continuous cycle sewing.
- Expandable feed dog height and wide range of tilt adjustment.
- Feed dog can be adjusted range from upward, horizontal, downward, and adapt to high and low segment sewing function.
- Titanium coated inner hook runs cooler and smoother.
- Special new Feed Design is suitable for a variety of fabrics and efficiently sewing complex patterns.
- Hook axis compensation system which assures that the phase position of the hook tip is always in optimum position.
- Microprocessor control and multiple stitch patterns.
- Combination zig-zag and straight stitcher
- Reverse feed and adjustable reverse stitch length

Patterns	Straight stitch	Standard zigzag	2 steps zigzag	3 steps zigzag	Scallop (left)				Scallop (right)				Blind stitch (left)	
					1	2	3	4	1	2	3	4	Standard type	L-type
Pattern														
Stitch number	-	24	4	6	24	12	24	24	24	12	24	24	Straight line: max. 99 stitches	

**16 basic patterns, such as straight stitch, two and three scallops, blind stitch and L-type stitch.**  
Internally installed zigzag pattern input function, it also provides L-type blind stitch.

## SPECIFICATIONS

Speed, Max. (S.P.M.)*	4500	Stitch Length, Max.	5 s.p.i. (5 mm)	
Footlift	by Hand	15/64" (6 mm)	Needle	DP x 5
	by Knee	7/32" (5.5 mm)	Stitch Width Max.	11/32" (9 mm)
	Auto footlifter - Optional		Workspace	11-13/16" (300 mm)
Needle Bar Stroke	1 6/25" (31.5 mm)	Weight	165 lbs (75 kg)	

\* Speed depends on width of zig-zag, material and thread.

Specifications subject to change without notice.

©2020 Consew USA -0520