

**KANSAI**  
SPECIAL®



**NR9803GALK-ABH3**

### NR9803GALK-ABH3

3 Needle, 5 Thread, Cylinder bed Flat lock Fully Automatic circular Bottom hemming machine

#### TECHNICAL SPECIFICATION











- Application : Polo Shirt / T Shitrt / Circular Hemming.
- Thread Watcher : Machine Will stop automatically once the thread breaks.
- Thread Trimmer : Thread Trims Automatically.
- Air Wiper gives clean stitch quality on the top side of fabric.
- Hem Length : 38cm to 80cm (15" to 30")
- Hem Width : 17mm to 24mm.
- Speed : 4000 Running RPM.
- Fabric Stacking System .
- Electronic Motor Edge control system.
- Noise Level of a machine working at 4000rpm is Lpa-84dB.
- LCD Monitor Sensitive color display adjusts the sewing step setting.
- Stitch Length is 6-16 / Inch.
- Individual Pulse motor will keep the knife position down at the end of operation to avoid any fabric damage while removing.

#### PRODUCTIVITY

- Production Capacity : 250 Pcs to 300 Pcs / Hour (12 Stitch/ inch)
- Single worker can easily work on two machines at the same time.
- Unskilled Operator can Produces High Productivity with good quality.
- Double side Seam will come same direction.
- Easily adjustable for a different hem length.
- Consistant Sewing Standards with high Quality.
- Increased Productivity and Less Rejection of Garments due to Consistant Sewing quality.

#### POWER / AIR PRESSURE SPECIFICATION

- Single Phase / Voltage : 220 watts.
- Power Consumption : 1.5KW
- Air Pressure : 6-7 Bar

Model Name	Application	Material	Needle	No.of threads	Needle gauge	Needle bar stroke	Stitch length	Diff. feed ratio	Presser foot lift	Maximum Speed
										
NR9803GALK-ABH3	Knit	light to medium	UYx128GAS # 10-14	5	3/16, 7/32, 1/4	33	6-16 stitch/inch	0.3-2.9	6	4000